

DARWIN 1-STAGE POINT OF ENTRY SYSTEM

DARWIN DUAL SEDIMENT AND CARBON CARTRIDGES

DARWIN Dual Sediment and Carbon Cartridges are a unique, premium cartridge that utilizes several of the Pentair core competencies by merging technologies into one cartridge in order to bring customers a quality product.

DARWIN Dual Sediment and Carbon Cartridges offer the effective chlorine taste & odour reduction found in traditional carbon blocks, joined with the superior sediment reduction to resist premature plugging. These dual purpose cartridges are well-suited for a wide range of applications.



DETAILED SPECIFICATIONS 1-STAGE POINT OF ENTRY SYSTEM CARTRIDGES:

Model	DWWAT001DFX
Part number	655152-43
Maximum dimensions (mm)	117.60 x 508.89
Rating (nominal)*	10μ
Initial ΔP (PSI) @ Flow Rate (GPM)	1.0psi @ 4.0 gpm (0.07 bar @ 15.14 Lpm)
Chlorine taste & odour reduction @ flow rate	30,000 gal @ 4.0 gpm (113,562 L @ 15.14 Lpm)
Exterior Filter Media	Polypropylene Polyspun
Endcaps	Polypropylene
Temperature Rating	5°C to 50°C
Interior Filter Media	Carbon Block
Gaskets	Buna-N



The DFX Series Diamond Flow cartridges are Tested and Certified by NSF International to NSF/ANSI Standard 42 for material requirements only.